

LUBEX PRIMUS EC 15W-40

HIGH PERFORMANCE MOTOR OIL

PRODUCT DESCRIPTION

It is the high performance motor oil produced by blending mineral base oils and special additives and developed to provide high protection and lubrication performance. It can be used in four seasons.

APPLICATION/ USAGE

It is suitable for use in gasoline, LPG and diesel engines of passenger cars and light commercial vehicles in all modern technology vehicles.

ADVANTAGES/ BENEFITS

- Provides constant lubrication in all climate and road conditions. Therefore it can be used safely in all four seasons.
- Provides low oil consumption by its perfect viscosity control.
- Protects the engine against rust and corrosion.
- Prevents accumulation of ash and residue in the engine by its special additives. It improves performance and prolongs life of engine by keeping

the critical components of engine clean.

- Minimizes the wear on motor during start-up and warm-up by providing a durable oil film at any temperature and climate conditions.

SPECIFICATIONS/ APPROVALS

API SL/CF

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	15W-40	-
Density (15°C, g/cm ³)	0,886	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14,1	ASTM D 445
Viscosity Index	130	ASTM D 2270
Flash Point (°C)	230	ASTM D 92
Pour Point (°C)	-21	ASTM D 97
TBN (mgKOH/g)	6,8	ASTM D 2896
CCS (-20°C, cP)	5700	ASTM D 5293

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2021.03.11



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr