

# LUBEX PRIMUS MV 10W-40

## HIGH PERFORMANCE SYNTHETIC MOTOR OIL

### PRODUCT DESCRIPTION

It is the synthetic technology motor oil which provides high protection in gasoline, LPG, passenger diesel and light commercial vehicles in difficult road conditions where stop-and-go driving conditions are very frequent.

### APPLICATION/ USAGE

It is suitable for use in engines of gasoline, LPG, passenger diesel and light commercial vehicles. It can be used without any problem at all modern technology vehicle engines with injection, turbocharged and multi-valve. It is especially recommended for 4-wheeler modern passenger cars, such as caravans and SUVs.

### ADVANTAGES/ BENEFITS

- Provides constant lubrication at all types of weather and road conditions therefore it can be used safely in four seasons.
- Protects the engine against wear, especially in stop-and-go conditions.
- Increases the engine performance and prolongs its life through cleaning the critical parts of engine.
- Provides excellent engine protection against the formation of soot and sediment due to its excellent cleaning power.
- Protects the engine against wear and corrosion with the help of its special additives and extends

the engine life.

- Minimizes wear on engine during start-up and warm-up due to creating a durable oil film on the engine parts in all climate and temperature conditions.

### SPECIFICATIONS/ APPROVALS

API SN/CF  
ACEA A3/B4  
FIAT 9.55535-G2  
MB 229.3, MB 229.1  
RN 0710, RN 0700  
VW 501.01 / 505.00

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	10W-40	-
Density (15°C, g/cm <sup>3</sup> )	0,868	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14,5	ASTM D 445
Viscosity Index	150	ASTM D 2270
Flash Point (°C)	220	ASTM D 92
Pour Point (°C)	-30	ASTM D 97
TBN (mgKOH/g)	10	ASTM D 2896
CCS (-25°C, cP)	6500	ASTM D 5293
HTHS (150°C, cP)	4,3	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021 10.27



**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.  
Gebze OSB Mah. İhsan Dede Cad.  
No: 125/1, 41400 Gebze, Kocaeli, Turkey  
T +90 262 751 02 92 F +90 262 751 01 98  
info@lubex.com.tr - lubex.com.tr